



Standard Test Methods for Appearance of Admixtures Containing Halogenated Organic Solvents¹

This standard is issued under the fixed designation D 3741; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ε) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 These test methods cover the visual determination of the physical appearance of admixtures containing halogenated hydrocarbons. These test methods are qualitative test methods.

1.2 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.*

2. Significance and Use

2.1 These test methods are useful for determining the appearance of halogenated hydrocarbons and their admixtures.

TEST METHOD A—USING NESSLER TUBES

3. Apparatus

3.1 *Color Comparison Tube*, 100-mL tall-form Nessler. Tubes should be selected so that the height of the 100-mL graduation mark is 275 to 295 mm above the bottom of the tube with ground glass cap.

3.2 *Viewing Stand*, constructed to permit visual observation of light transmitted through the Nessler tube in the direction of its longitudinal axis. The viewing stand should be constructed so that white light is passed through or reflected off a white glass plate and directed with uniform intensity through the tube, and should be shielded so that no light enters the tube from the side.

4. Procedure

4.1 Vigorously shake the sample to distribute any solid matter that may be deposited on the bottom of the container. Transfer the sample to the tube and cap the tube.

4.2 Place the tube in the viewing stand. Observe the sample through the longitudinal direction of the tube, looking for suspended particles, floaters, sediment, turbidity, foaming, or free water.

5. Report

5.1 Report extraneous contaminants as suspended or floating matter, sediments, turbidity, or free water.

6. Precision and Bias

6.1 This is a pass/fail test. It is not the intent of this test method to provide a method for determining extraneous matter on a quantitative basis.

7. Keywords

7.1 appearance; chlorinated organic solvents; organic solvents; solvents

TEST METHOD B—USING A CLEAR, COLORLESS GLASS BOTTLE

8. Apparatus

8.1 *Clear, Colorless Sample Bottle*.

8.2 *White Background and Black Background*, in well-lighted area.

9. Procedure

9.1 Vigorously shake the sample to distribute any solid matter that may be deposited on the bottom of the container. If the sample is not in a clear, colorless bottle, transfer it to one in an exhaust hood. Immediately place the sample in front of a white background in a well-lighted area. Examine for suspended particles, floaters, sediment, turbidity, or free water.

9.2 Vigorously shake the sample again. Immediately place the sample in front of a black background in a well-lighted area. Examine for suspended particles, floaters, sediment, turbidity, foaming, or free water.

10. Report

10.1 Report extraneous contaminants as suspended or floating matter, sediments, turbidity, or free water.

11. Precision and Bias

11.1 This is a pass/fail test. It is not the intent of this test method to provide a method for determining extraneous matter on a quantitative basis.

¹ These test methods are under the jurisdiction of ASTM Committee D26 on Halogenated Organic Solvents and Fire Extinguishing Agents and are the direct responsibility of Subcommittee D26.04 on Test Methods.

Current edition approved Jan. 10, 2000. Published April 2000. Originally published as D 3741 – 85. Last previous edition D 3741 – 95.

12. Keywords

12.1 appearance; chlorinated organic solvents; organic solvents; solvents

ASTM International takes no position respecting the validity of any patent rights asserted in connection with any item mentioned in this standard. Users of this standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, are entirely their own responsibility.

This standard is subject to revision at any time by the responsible technical committee and must be reviewed every five years and if not revised, either reapproved or withdrawn. Your comments are invited either for revision of this standard or for additional standards and should be addressed to ASTM International Headquarters. Your comments will receive careful consideration at a meeting of the responsible technical committee, which you may attend. If you feel that your comments have not received a fair hearing you should make your views known to the ASTM Committee on Standards, at the address shown below.

This standard is copyrighted by ASTM International, 100 Barr Harbor Drive, PO Box C700, West Conshohocken, PA 19428-2959, United States. Individual reprints (single or multiple copies) of this standard may be obtained by contacting ASTM at the above address or at 610-832-9585 (phone), 610-832-9555 (fax), or service@astm.org (e-mail); or through the ASTM website (www.astm.org).